



Precision engineered for municipal or commercial use.

The cost effective solution for trash hauling.

Our DynaHauler®/AT tipper trailer is an economical, user-friendly work-horse that will provide you with years of dependable service and a steady stream of profits. These lightweight trailers are loaded with standard features like fully enclosed wiring in conduit from the front to the rear, a front service compartment to easily access air lines and wiring, and the best upper coupler and tipper bumper in the industry.

Rely on our experience.

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 55+ years of experience to build you the dump trailers you want - we'll build them to your specification and application.

ALUMINUM
TIPPER
TRAILER

DYNAHAULER®

ISO 9001:2015 Certified.
Quality products,
quality workmanship.

*J&J Truck Bodies & Trailers
is a division of
Somerset Welding & Steel, Inc.*

**J&J TRUCK BODIES
& TRAILERS®**
Built for the Long Haul®

Call today! 800.777.2671
www.jjbodies.com

SPECIFICATIONS & DIMENSIONAL DATA FOR ALUMINUM TIPPER TRAILER



We can easily outfit your trailer with optional manual or electric tarps.



Standard bumper with extra wide blocks protects the trailer from damage due to many years of tipping.

ALUMINUM STANDARD SPECIFICATIONS*

- Capacity:** 115 cubic yards.
- Length:** 48'
- Width:** 102".
- Side Height:** 100".
- King Pin Setting:** 36".
- Bulkhead:** 3/16" 5454-H34.
- Side panels:** 3/16" 5454-H34.
- Floor:** 1/4" 5454-H34, (3/8" last 10' available).
- Understructure:** 4" x 4" boxed cross members on 16" centers. Suspension and landing gear reinforced with crossmembers on 12" centers and boxed interlacing.
- Lighting:** Standard Truck-Lite package.
- Tailgate:** Top offset hardware, 5/32" 5454-H34 base sheet, 3 horizontal braces, full rubber seal, 2 slop latches, 3/4 ladder, 2 upper grab handles and two side steps.

- Suspension Sub-frame:** 12" aluminum channel long members with 5/8" flanges. 10" aluminum channel crossmembers with 5/8" flanges.
- Bumper:** High strength, light weight 175,000 yield HARDOX shell, with 10" wide, heavy duty, laminated bumper blocks, center tow pin and bolt on step.
- Suspension:** Reyco 21B Single leaf, 50,000 lb.
- Axles:** Lightweight Dana 22,500lb. 1/2" wall.
- Wiring/Air lines:** Fully enclosed in conduit from suspension into the front service compartment.
- Brakes:** Haldex slack adjusters.
- Landing Gear:** Holland 5100 series (140,000 lb. static load).
- Catwalk:** 68" long, 20" wide aluminum catwalk.
- Ladders:** One aluminum ladder on the drivers side front bulkhead.
- Access steps:** Cast aluminum steps, driver side (inside trailer) mounted on front corner.

Available with: 

*Standard specifications may vary according to customer's preferences and requirements. Many options available.

Call your J&J sales representative today!



D.O.T. Registered • A.S.M.E. Certified • National Board Registered

Distributed by:

ISO 9001:2015 Certified
"Our Commitment to Quality"



10558 Somerset Pike
Somerset, PA 15501 USA
Phone: 814.444.3400
Fax: 814.443.2621
Toll Free: 800.777.2671 (USA only)
Email: sales@jjbodies.com
www.jjbodies.com

Rev: 0916-1