

SPO

CLOSED TOP PUSH OUT TRAILERS

DYNHAULER

ISO 9001:2015 Certified.
Quality products,
quality workmanship.

*J&J Truck Bodies & Trailers
is a division of
Somerset Welding & Steel, Inc.*



*Open top push outs also
available.*

*Trailer shown with closed top and
Dutch door side swing tailgate with
side grab pockets.*

Ideal for hauling municipal refuse.

The unique J&J push out transfer trailer ejects horizontally eliminating the dangerous problem of tipping or rollovers at landfills that oftentimes have uneven terrain. The SPO trailer is available in 65, 75, 85, and 92 cu. yds. J&J specializes in waste handling trailers and equipment including tipper trailers, live floor trailers, and dump trailers.

Rely on our experience.

There's no substitute for a truck body built by the experts at J&J Truck Bodies & Trailers. We don't cut corners and we don't compromise on quality. Rely on our 55+ years of experience to build you the dump trailers you want - we'll build them to your specification and application.

**J&J TRUCK BODIES
& TRAILERS**
Built for the Long Haul®

Call today! 800.777.2671
www.jjbodies.com

SPECIFICATIONS & DIMENSIONAL DATA FOR STEEL PUSH OUT TRAILERS



Tractor hook-ups and hydraulic controls located in one area for ease of operation. Trailer shown with optional trailer mounted hydraulic tank.



Ejector ram cylinder is sized to completely unload trailer and the replaceable UHMW wipers on top and sides of ejector ram provide superior clean-out.

STEEL STANDARD SPECIFICATIONS*

Length: 39' or 45'.
Inside Height: 76", 88" or 96".
Side Panels: Front 12 ga., rear 1/3 10 ga. high-tensile.
Floor: 3/16" high-tensile.
Side Posts: 12 ga. high-tensile, spacing 18" rear 1/3, 24" center 1/3, 32" front 1/3.
Crossmembers: 4" JR I-beam on 12" centers.
Ejector: 10 ga. high-tensile face plate, 3/16" & 1/4" high-tensile, 4" boxed brace members.
Hydraulic System: To suit tractor.

Rear Door: Dutch, barndoor or door-on-door.
Suspension: Tandem REYCO-52,000# capacity.
Hub & Drum Assembly: Cast steel hub piloted.
Rims: 8.25 x 22.5.
Tires: 11R22.5, 14 ply.
Axles: 25,000# capacity.
Lighting: Truck-Lite® sealed harness.
Landing Gear: Holland MK-V 200,000# static load, 62,500# lift.
King Pin: Holland T-880.
Cylinders: 39'-8" 5 stage; 45'-9" 5 stage.

Available with: **J&J BODY ARMOR**



Steel push out trailers can safely unload at landfills where ground conditions are not always ideal.

STANDARD FEATURES

High-tensile steel construction with 3/16" floor for greater strength.
 Tailgates available: one piece, side hinged door (standard); two-piece, side hinged door or top hinged, hydraulically operated (optional).
 Power sources: wet line with tractor PTO; trailer mounted auxiliary power unit; self-contained auxiliary power unit.
 Shock absorbing landing gear.

POPULAR OPTIONS

Open Top model available.
 Auxiliary engine power (gas or diesel).
 100" opening self compacting.
 Special tailgates.
 Lightweight models available.
 Special tires, wheels, and rims.

High Hard Steel 450 steel floor and sides.
 Special paint.
 39'-9" 5 stage cylinder.
 Optional 15" or 30" king pin location.

*Standard specifications may vary according to customer's preferences and requirements. Many options available.
 Call your J&J sales representative today!

DIMENSIONAL DATA

MODEL:	SPO65B	SPO75B	SPO85B
CAPACITY:	65 cubic yard	75 cubic yard	85 cubic yard
LENGTH:	40 feet	40 feet	45 feet
WIDTH:	95, 7/8 inches	95, 7/8 inches	95, 7/8 inches
HEIGHT:	140 inches	152 inches	152 inches
INSIDE HEIGHT:	84, 1/2 inches	96 inches	96 inches



D.O.T. Registered • A.S.M.E. Certified • National Board Registered

Distributed by:

ISO 9001:2015 Certified
 "Our Commitment to Quality"



J&J TRUCK BODIES & TRAILERS®
 Built for the Long Haul®

10558 Somerset Pike
 Somerset, PA 15501 USA
 Phone: 814.444.3400
 Fax: 814.443.2621
 Toll Free: 800.777.2671 (USA only)
 Email: sales@jjbodies.com
 www.jjbodies.com

Rev: 0916-1